



Luxury Audio





Forhandlerprisliste - Danmark - 12. Februar 2015







| Model | Product Description | Part # | SALGSPRIS/stk |
|--|---|--|---------------|
| Salon2  | 4-Way Floorstanding Loudspeaker <ul style="list-style-type: none"> • Three 8" (20 cm) Titanium cone woofers • 6 ½" (16.5 cm) Titanium cone mid-woofer • 4" (10 cm) Titanium cone midrange • 1" (2.5 cm) Beryllium tweeter • Sensitivity: 86.4 dB SPL with 2.83 V @ 1m (4 pi anechoic) • Impedance: 6 Ohms (nominal); 3.7 Ohms (minimum @ 90 Hz) • Frequency range: 23Hz - 45kHz (-3dB) • Dimensions (H x W x D): 53.3" x 14" x 23" (135.4 cm x 35.6 cm x 58.4 cm) • Weight: 146 lb (66.3 kg) / shipping weight: 178 lb (80.7 kg) • Piano black or mahogany finish | NSALON2 PIANO BLK (Piano Black Gloss) NSALON2 MAHOGANY (Mahogany Wood) | DK 98.000,00 |
| Studio2  | 3-Way Floorstanding Loudspeaker <ul style="list-style-type: none"> • Two 8" (20 cm) Titanium cone woofers • 5 ¼" (13.3 cm) Titanium cone midrange • 1" (2.5 cm) Beryllium tweeter • Sensitivity: 87.7 dB SPL with 2.83 V @ 1m (4 pi anechoic) • Impedance: 6 Ohms (nominal); 3.7 Ohms (minimum @ 90 Hz) • Frequency range: 32Hz - 45kHz (-3dB) • Dimensions (H x W x D): 46.3" x 13.8" x 20.5" (117.6 cm x 35.1 cm x 52.1 cm) • Weight: 112 lb (50.9 kg) / shipping weight: 140 lb (63.5 kg) • Piano black or mahogany finish | STUDIO2 PIANO BL (Piano Black Gloss) NSTUDIO2 MAHOGANY (Mahogany Wood) | DK 69.000,00 |
| Gem2  | 3-Way Bookshelf Loudspeaker <ul style="list-style-type: none"> • 8" (20 cm) Titanium cone woofer • 4" (10 cm) Titanium cone midrange • 1" (2.5 cm) Beryllium tweeter • Sensitivity: 86.4 dB SPL with 2.83 V @ 1m (4 pi anechoic) • Impedance: 6 Ohms (nominal); 3.4 Ohms (minimum) • Frequency range: 70Hz - 45kHz (-3dB) • Dimensions (H x W x D): 24.2" x 12" x 5.4" (61.5 cm x 30.5 cm x 13.7 cm) • Weight: 32 lb (14.5 kg) / shipping weight: 38 lb (17.2 kg) • Piano black or mahogany finish | NGEM2 PIANO BLK (Piano Black Gloss) NGEM2 MAHOGANY (Mahogany Wood) | DK 44.000,00 |
| | Optional Tabletop Stand for Gem2 <ul style="list-style-type: none"> • Adds 1.6" (4.1 cm) to Gem2 height • Piano black finish | N365208-001 | DK 471,00 |
| | Optional Floor Pedestal for Gem2 (shown) <ul style="list-style-type: none"> • Adds 46" (117 cm) to Gem2 height • Piano black finish | NGEM2 STAND | DK 7.000,00 |
| Model | Product Description | Part # | SALGSPRIS/stk |
| Voice2  | 3-Way Center Channel Loudspeaker <ul style="list-style-type: none"> • Two 8" (20 cm) Titanium cone woofers • 5 ¼" (13.3 cm) Titanium cone midrange • 1" (2.5 cm) Beryllium tweeter • Sensitivity: 89 dB SPL with 2.83 V @ 1m (4 pi anechoic) • Impedance: 6 Ohms (nominal); 3.6 Ohms (minimum @ 90 Hz) • Frequency range: 60Hz - 45kHz (-3dB) • Dimensions (H x W x D): 14.7" x 25.5" x 14" (37.3 cm x 64.8 cm x 35.6 cm) • Weight: 62 lb (28.2 kg) / shipping weight: 74.5 lb (33.8 kg) • Piano black or mahogany finish | NVCE2 PIANO BLK (Piano Black Gloss) NVCE2 MAHOGANY (Mahogany Wood) | DK 69.000,00 |




Ultima2 Loudspeaker Series



| | | | |
|--|--|-------------|-------------|
| | Optional Floor Pedestal for Voice2 <ul style="list-style-type: none">• Adds 24.2" (61.4 cm) to Voice2 height• Piano black finish | NVCE2 STAND | DK 5.200,00 |
|--|--|-------------|-------------|

| Model | Product Description | Part # | SALGSPRIS/stk |
|---|---|---|--------------------|
| F208  | <p>3-Way Floorstanding Tower Loudspeaker</p> <ul style="list-style-type: none"> • Dual 8" (20 cm) Aluminum cone, cast-frame woofers • 5.25" (13.3 cm) Aluminum cone, cast-frame midrange • 1" (2.5 cm) Aluminum tweeter with acoustic lens waveguide • Recommended amplifier power range: 50 – 350 watts • Low-frequency extension: 23Hz (–10dB); 27Hz (–6dB); 31Hz (–3dB) • Nominal impedance: 8 Ohms • Sensitivity: 88.5dB (2.83V/1m) • Enclosure type: bass-reflex via front-mounted port • Controls: low-frequency contour; high-frequency level • Inputs: dual gold-plated binding posts with shorting straps • Dimensions (H x W x D): 46.5" x 11.8" x 14.8" (118.2 cm x 30 cm x 37.5 cm) • Net weight: 80 lb (36 kg) • Piano black or high gloss walnut | <p>F208 BK (Piano Black)</p> <p>F208 WA (Walnut)</p> | DK 23.900,00 |
| F206  | <p>3-Way Floorstanding Tower Loudspeaker</p> <ul style="list-style-type: none"> • Dual 6.5" (16.5 cm) Aluminum cone, cast-frame woofers • 5.25" (13.3 cm) Aluminum cone, cast-frame midrange • 1" (2.5 cm) Aluminum tweeter with acoustic lens waveguide • Recommended amplifier power range: 50 – 200 watts • Low-frequency extension: 30Hz (–10dB); 34Hz (–6dB); 42Hz (–3dB) • Nominal impedance: 8 Ohms • Sensitivity: 88dB (2.83V/1m) • Enclosure type: bass-reflex via front-mounted port • Inputs: gold-plated binding posts • Dimensions (H x W x D): 41.4" x 9.8" x 13.7" (105.1 cm x 24.9 cm x 34.7 cm) • Net weight: 58 lb (26 kg) • Piano black, piano white, or high gloss walnut | <p>F206 BK (Piano Black)</p> <p>F206 WA (Walnut)</p> <p>F206 WH (White)</p> | DK 16.900,00 |
| M106  | <p>2-Way Bookshelf Monitor Loudspeaker</p> <ul style="list-style-type: none"> • 6.5" (16.5 cm) Aluminum cone, cast-frame woofer • 1" (2.5 cm) Aluminum tweeter with acoustic lens waveguide • Recommended amplifier power range: 50 – 150 watts • Low-frequency extension: 39Hz (–10dB); 54Hz (–6dB); 59Hz (–3dB) • Nominal impedance: 8 Ohms • Sensitivity: 87dB (2.83V/1m) • Enclosure type: bass-reflex via rear-mounted port • Inputs: gold-plated binding posts • Dimensions (H x W x D): 15" x 8.3" x 11" (38.1 cm x 21 cm x 27.8 cm) • Net weight: 19 lb (8 kg) • Piano black or high gloss walnut | <p>M106 BK (Piano Black)</p> <p>M106 WA (Walnut)</p> | DK 8.800,00 |
| M Stand  | <p>Optional Floor Pedestal for M105/M106</p> <ul style="list-style-type: none"> • Dimensions (H x W x D): 25" x 9.4" x 11.5" (63.5 cm x 23.8 cm x 29.1 cm) • Net weight: 8 lb (4 kg) • Black or white finish • Pair packed | <p>M STAND BK (Piano Black)</p> <p>M STAND WH (White)</p> | DK 3.900,00 PAR |

| Model | Product Description | Part # | SALGSPRIS/stk |
|--|--|--|--|
| M105  | 2-Way Bookshelf Monitor Loudspeaker <ul style="list-style-type: none"> • 5.25" (13.3 cm) Aluminum cone, cast-frame woofer • 1" (2.5 cm) Aluminum tweeter with acoustic lens waveguide • Recommended amplifier power range: 50 – 120 watts • Low-frequency extension: 44Hz (–10dB); 56Hz (–6dB); 60Hz (–3dB) • Nominal impedance: 8 Ohms • Sensitivity: 86dB (2.83V/1m) • Enclosure type: bass-reflex via rear-mounted port • Inputs: gold-plated binding posts • Dimensions (H x W x D): 14" x 7.9" x 9.8" (35.6 cm x 20 cm x 24.8 cm) • Net weight: 16 lb (7 kg) • Piano black, piano white, or high gloss walnut | M105 BK (Piano Black) M105 WA (Walnut) M105 WH (White) | DK 6.800,00 |
| | M Stand  | Optional Floor Pedestal for M105/M106 <ul style="list-style-type: none"> • Dimensions (H x W x D): 25" x 9.4" x 11.5" (63.5 cm x 23.8 cm x 29.1 cm) • Net weight: 8 lb (4 kg) • Black or white finish • Pair packed | M STAND BK (Piano Black) M STAND WH (White) |
| C208  | 3-Way Center Channel Loudspeaker <ul style="list-style-type: none"> • Dual 8" (20 cm) Aluminum cone, cast-frame woofers • 4" (10 cm) Aluminum cone, cast-frame midrange • 1" (2.5 cm) Aluminum tweeter with acoustic lens waveguide • Recommended amplifier power range: 50 – 350 watts • Low-frequency extension: 34Hz (–10dB); 41Hz (–6dB); 50Hz (–3dB) • Nominal impedance: 8 Ohms • Sensitivity: 89dB (2.83V/1m) • Enclosure type: sealed • Controls: low-frequency contour; high-frequency level • Inputs: dual gold-plated binding posts with shorting straps • Dimensions (H x W x D): 11.8" x 28.9" x 13.8" (30 cm x 73.5 cm x 35 cm) • Net weight: 52 lb (23 kg) • Piano black or high gloss walnut | C208 BK (Piano Black) C208 WA (Walnut) | DK 17.500,00 |
| | C Stand  | Optional Floor Pedestal for C205/C208 <ul style="list-style-type: none"> • Dimensions (H x W x D): 10.8" x 21.4" x 11.9" (27.5 cm x 54.4 cm x 30.1 cm) • Net weight: 15 lb (7 kg) • Black or white finish | C STAND BK (Piano Black) C STAND WH (White) |
| C205  | 2-Way Center Channel Loudspeaker <ul style="list-style-type: none"> • Dual 5.25" (13.3 cm) Aluminum cone, cast-frame woofers • 1" (2.5 cm) Aluminum tweeter with acoustic lens waveguide • Recommended amplifier power range: 50 – 120 watts • Low-frequency extension: 46Hz (–10dB); 62Hz (–6dB); 80Hz (–3dB) • Nominal impedance: 8 Ohms • Sensitivity: 89dB (2.83V/1m) • Crossover frequencies: 1.7kHz • Enclosure type: sealed • Inputs: gold-plated binding posts • Dimensions (H x W x D): 7.9" x 21" x 11.5" (20 cm x 53.2 cm x 29.2 cm) • Net weight: 26 lb (12 kg) • Piano black, piano white, or high gloss walnut | C205 BK (Piano Black) C205 WA (Walnut) C205 WH (White) | DK 8.500,00 |
| | C Stand  | Optional Floor Pedestal for C205/C208 <ul style="list-style-type: none"> • Dimensions (H x W x D): 10.8" x 21.4" x 11.9" (27.5 cm x 54.4 cm x 30.1 cm) • Net Weight: 15 lb (7 kg) • Black or white finish | C STAND BK (Piano Black) C STAND WH (White) |

| Model | Product Description | Part # | SALGSPRIS/stk |
|---|--|--|---------------------|
| <p>S206</p>  | <p>2-Way Surround Loudspeaker</p> <ul style="list-style-type: none"> • Dual 6.5" (16.5 cm) Aluminum cone, cast-frame woofers • 1" (2.5 cm) Aluminum tweeter with acoustic lens waveguide • Recommended amplifier power range: 50 – 150 watts • Low-frequency extension: 52Hz (–10dB); 58Hz (–6dB); 65Hz (–3dB) • Nominal impedance: 8 Ohms • Sensitivity: 89dB (2.83V/1m) • Crossover frequency: 1.4kHz • Enclosure type: sealed • Inputs: gold-plated binding posts • Dimensions (H x W x D): 13.5" x 15.8" x 8.5" (34.3 cm x 40 cm x 21.6 cm) • Net weight: 16 lb (7 kg) • Matte black | <p>S206MB (Matte Black)</p> | <p>DK 7.800,00</p> |
| <p>B112</p>  | <p>1000-watt Powered Subwoofer</p> <ul style="list-style-type: none"> • 12" (30 cm) Aluminum cone, cast-frame woofer • Line-level XLR and RCA in/out • Dimensions (H x W x D): 17.8" x 15.7" x 15.6" (45.2 cm x 39.9 cm x 39.6 cm) • Net weight: 70 lb (32 kg) • Piano black or high gloss walnut | <p>B112 BKE (Piano Black, 230 volt)</p> <p>B112 WAE (Walnut, 230 volt)</p> | <p>DK 25.990,00</p> |
| <p>B110</p>  | <p>1000-watt Powered Subwoofer</p> <ul style="list-style-type: none"> • 10" (25.4 cm) Aluminum cone, cast-frame woofer • Line-level XLR and RCA in/out • Dimensions (H x W x D): 16.2" x 14.2" x 12.6" (41.2 cm x 36.1 cm x 32 cm) • Net weight: 56 lb (25 kg) • Piano black, piano white or high gloss walnut | <p>B110 BKE (Piano Black, 230 volt)</p> <p>B110 WAE (Walnut, 230 volt)</p> <p>B110 WHE (White, 230 volt)</p> | <p>DK 19.900,00</p> |





In-Ceiling and In-Wall Architectural Loudspeakers



| Model | Product Description | Part # | SALGSPRIS/stk |
|--|--|------------|---------------|
| C540  | 4" Micro-Ceramic Composite (MCC) cone, cast-Aluminum frame woofer <ul style="list-style-type: none"> • 1" Aluminum dome swiveling tweeter with waveguide • Mounting depth: 3.3" (8.4 cm) • Weight: 1.5 lb (0.7 kg) / shipping weight: 1.9 lb (0.9 kg) • Cutout dimensions (dia.): 3.5" (8.9 cm) • Includes both round and square zero-bezel magnetic grilles • Round grille finished dimension (dia.): 4.4" (11.2 cm) • Square grille finished dimensions (h x w): 4.4" x 4.4" (11.2 cm x 11.2 cm) • Roller Lock tool-free installation mechanism • Recommended amplifier power range: 10 - 80 watts • Nominal impedance: 8 Ohms • Frequency range: 180Hz - 20kHz (-3 dB); 150Hz - 30kHz -10dB • Compatible with wall material thickness: 0.5" – 0.9" (1.3cm – 2.3cm) | REVEL C540 | DK 1.499,00 |
| | Rough-In Bracket PCK4C – RIB for C540 In-Ceiling Loudspeaker | PCK4C | |
| | Fire-Rated Back-box Fire (1 hour) Rated Steel Back-box for C540 In-Ceiling Loudspeaker | FBB4C | DK 925,00 |
| C763L  | 7.8" x 3.4" Micro-Ceramic Composite (MCC) cone, diaphragm flat-panel woofer <ul style="list-style-type: none"> • Two 3.5" micro-ceramic composite (MCC) cone, cast-aluminum frame high-output midranges • 1" aluminum high-output tweeter with waveguide • 3-position HF level control • LF boundary compensation • Mounting depth: 5.7" (14.5 cm) • Weight: 4 lb (1.8 kg) / shipping weight: 5.2 lb (2.4 kg) • Cutout dimensions (dia.): 11.3" (28.7 cm) • Includes both round and square zero-bezel magnetic grilles • Round grille finished dimension (dia.): 12.5" (31.8 cm) • Square grille finished dimensions (h x w): 12.5" x 12.5" (31.8 x 31.8 cm) • Nominal impedance: 8 Ohms • Recommended amplifier power range: 10 - 200 watts • Sensitivity (2.83V/1m): 86 dB • Frequency range: 80Hz - 28kHz (-3 dB); 72Hz - 35kHz (-10dB) • Compatible with wall material thickness: 0.5" – 2.0" (1.3cm – 5.0cm) | C763L | DK 5.199,00 |
| | PCK10C – RIB for C763L In-Ceiling Loudspeaker | PCK10C | DK 239,00 |
| | Fire-Rated Back-box Fire (1 hour) and Plenum Rated Steel Back-box for C763L In-Ceiling Loudspeaker | FBB10C | DK 1.299,00 |
| C263LP  | Low Profile 6" Aluminum cone, cast-polymer frame woofer <ul style="list-style-type: none"> • 1" Aluminum dome swiveling tweeter with waveguide • Mounting depth: 2.72" (69.1mm) • Weight: 3.1 lb (1.41kg) / shipping weight: 4.6 lb (2.1kg) • Includes a round zero-bezel magnetic grille • Round grille finished dimension (Dia.): 9.1" (23.1cm) • Cutout dimensions (dia.): 8" (20.3 cm) • Nominal impedance: 8 Ohms • Recommended amplifier power range: 10 - 100 watts | C263LP | DK 1.599,00 |
| C283LP  | Low Profile 8" Aluminum cone, cast-polymer frame woofer <ul style="list-style-type: none"> • 1" Aluminum dome swiveling tweeter with waveguide • Mounting depth: 2.69" (68.3mm) • Weight: 3.9 lb (1.8 kg) / shipping weight: 5.9 lb (2.7 kg) • Includes round zero-bezel magnetic grille • Round grille finished dimension (dia.): 10.7" (27.2 cm) • Cutout dimensions (dia.): 9.6" (24.4 cm) • Nominal impedance: 8 Ohms • Recommended amplifier power range: 10 - 100 watts | C283LP | DK 1.999,00 |



In-Ceiling and In-Wall Architectural Loudspeakers








| Model | Product Description | Part # | SALGSPRISstk |
|--|--|--------|--------------|
| C263  | 6 ½" Aluminum cone, cast-polymer frame woofer <ul style="list-style-type: none"> • 1" Aluminum dome swiveling tweeter with waveguide • Mounting depth: 4.8" (12.2 cm) • Weight: 3.1 lb (1.41 kg) / shipping weight: 4.6 lb (2.1 kg) • Includes a round zero-bezel magnetic grille • Round grille finished dimension (dia.): 9.1" (23.1 cm) • Cutout dimensions (dia.): 8" (20.3 cm) • Nominal impedance: 8 Ohms • Recommended amplifier power range: 10 - 100 watts • Sensitivity: 86 dB (2.83V/1m) • Frequency range: 50 - 18 kHz (-3 dB); 36Hz - 20 kHz (-10dB) | C263 | DK 1.199,00 |
| C363  | 6 ½" Micro-Ceramic Composite (MCC) cone, cast-polymer frame woofer <ul style="list-style-type: none"> • 1" Aluminum dome swiveling tweeter with waveguide • Mounting depth: 4.8" (12.2 cm) • Weight: 1.6 lb (0.8 kg) / shipping weight: 2.4 lb (1.1 kg) • Cutout dimensions (dia.): 8" (20.3 cm) • Includes both round and square zero-bezel magnetic grilles • Nominal impedance: 8 Ohms • Recommended amplifier power range: 10 - 100 watts • Sensitivity: 86 dB (2.83V/1m) • Frequency range: 50 - 18 kHz (-3 dB); 36Hz - 20 kHz (-10dB) • Round grille finished dimension (dia.): 9.1" (23.1 cm) • Square grille finished dimensions (H x W): 9.1" x 9.1" (23 cm x 23 cm) | C363 | DK 1.999,00 |
| C563  | 6 ½" Micro-Ceramic Composite (MCC) cone, cast-Aluminum frame woofer <ul style="list-style-type: none"> • 1" Aluminum dome swiveling tweeter with waveguide • 3-position HF level control • Mounting depth: 4.9" (12.5 cm) • Weight: 2 lb (0.9 kg) / shipping weight: 2.7 lb (1.2 kg) • Cutout dimensions (dia.): 8" (20.3 cm) • Nominal impedance: 8 Ohms • Recommended amplifier power range: 10 - 130 watts • Sensitivity: 88 dB (2.83V/1m) • Frequency range: 50Hz - 25kHz (-3 dB); 35Hz - 30kHz (-10dB) • Includes both round and square zero-bezel magnetic grilles • Round grille finished dimension (dia.): 9.1" (23.1 cm) • Square grille finished dimensions (H x W): 9.1" x 9.1" (23.1 cm x 23.1 cm) | C563 | DK 2.799,00 |
| C763  | 6 ½" Micro-Ceramic Composite Cone (MCC), cast-Aluminum frame high-output woofer <ul style="list-style-type: none"> • 1" Aluminum dome swiveling high-output tweeter with waveguide • 3-position HF level control • LF boundary compensation • Mounting depth: 4.9" (12.5 cm) • Weight: 2.4 lb (1.1 kg) / shipping weight: 3.2 lb (1.5 kg) • Cutout dimensions (dia.): 8" (20.3 cm) • Nominal impedance: 8 Ohms • Recommended amplifier power range: 10 - 140 watts • Sensitivity: 88 dB (2.83V/1m) • Frequency range: 45Hz - 28kHz (-3 dB); 30Hz - 35kHz (-10dB) • Includes both round and square zero-bezel magnetic grilles • Round grille finished dimension (dia.): 9.1" (23.1 cm) • Square grille finished dimensions (H x W): 9.1" x 9.1" (23.1 cm x 23.1 cm) | C763 | DK 4.099,00 |
| Rough-in Bracket | RIB for all Cx63 6 ½" In-Ceiling Loudspeakers | PCK6C | |
| Fire-Rated Back-box | Fire (1 hour) and Plenum Rated Steel Back-box for all Cx63 6 ½" In-Ceiling Loudspeakers | FBB6C | DK 1.099,00 |

In-Ceiling and In-Wall Architectural Loudspeakers







| Model | Product Description | Part # | SALGSPRIS/stk |
|--|---|--------|---------------|
| C363DT  | 6 ½" Micro-Ceramic Composite (MCC) cone, cast-polymer frame woofer • Two 1" Aluminum dome tweeters with waveguides • Mounting depth: 4.8" (12.2 cm) • Weight: 1.9 lb (0.9 kg) / shipping weight: 2.6 lb (1.2 kg) • Cutout dimensions (dia.): 8" (20.3 cm) • Nominal impedance: 8 Ohms • Recommended amplifier power range: 10 - 120 watts (per channel) • Sensitivity: 88 dB (2.83V/1m) • Frequency range: 55Hz - 22kHz (-3 dB); 40Hz - 30kHz (-10dB) • Includes both round and square zero-bezel magnetic grilles • Round grille finished dimension (dia.): 9.1" (23.1 cm) • Square grille finished dimensions (H x W): 9.1" x 9.1" (23.1 cm x 23.1 cm) • C-2 fastening mechanism • Compatible with wall material thickness range: 0.5" – 2.0" (1.3 – 5.0 cm) | C363DT | DK 2.499,00 |
| C563DT  | 6 ½" Micro-Ceramic Composite (MCC) cone, cast-Aluminum frame woofer • Two 1" Aluminum dome tweeters with waveguides • 3-position HF level control • Mounting depth: 4.9" (12.5 cm) • Weight: 2.2 lb (1 kg) / shipping weight: 3 lb (1.4 kg) • Cutout dimensions (dia.): 8" (20.3 cm) • Nominal impedance: 8 Ohms • Recommended amplifier power range: 10 - 130 watts (per channel) • Sensitivity: 88 dB (2.83V/1m) • Frequency range: 55Hz - 28kHz (-3 dB); 30Hz - 35kHz (-10dB) • Includes both round and square zero-bezel magnetic grilles • Round grille finished dimension (dia.): 9.1" (23.1 cm) • Square grille finished dimensions (H x W): 9.1" x 9.1" (23.1 cm x 23.1 cm) • C-2 fastening mechanism • Compatible with wall material thickness range: 0.5" – 2.0" (1.3 – 5.0 cm) | C563DT | DK 3.299,00 |
| Rough-in Bracket | RIB for all Cx63 6 ½" In-Ceiling Loudspeakers | PCK6C | DK 220,00 |
| Fire-Rated Back-box | Fire (1 hour) and Plenum Rated Steel Back-box for all Cx63 6 ½" In-Ceiling Loudspeakers | FBB6C | DK 999,00 |

| Model | Product Description | Part # | SALGSPRIS/stk |
|--|---|--------|---------------|
| C283  | 8" Aluminum cone, cast-polymer frame woofer <ul style="list-style-type: none"> • 1" Aluminum dome swiveling tweeter with waveguide • Mounting depth: 5.2" (13.2 cm) • Weight: 3.9 lb (1.8 kg) / shipping weight: 5.9 lb (2.7 kg) • Includes round zero-bezel magnetic grille • Round grille finished dimension (dia.): 10.7" (27.2 cm) • Cutout dimensions (dia.): 9.6" (24.4 cm) • Nominal impedance: 8 Ohms • Recommended amplifier power range: 10 - 100 watts • Sensitivity: 87 dB (2.83V/1m) • Frequency range: 36 - 18 kHz (-3 dB); 28Hz - 20 kHz (-10dB) | C283 | DK 1.649,00 |
| C383  | 8" Micro-Ceramic Composite (MCC) cone, cast-polymer frame woofer <ul style="list-style-type: none"> • 1" Aluminum dome swiveling tweeter with waveguide • Mounting depth: 5.2" (13.2 cm) • Weight: 2.1 lb (1 kg) / shipping weight: 3.1 lb (1.4 kg) • Cutout dimensions (dia.): 9.6" (24.4 cm) • Nominal impedance: 8 Ohms • Recommended amplifier power range: 10 - 125 watts • Sensitivity: 87 dB (2.83V/1m) • Frequency range: 45Hz - 22kHz (-3 dB); 35Hz - 30kHz (-10dB) • Includes both round and square zero-bezel magnetic grilles • Round grille finished dimension (dia.): 10.7" (27.2 cm) • Square grille finished dimensions (H x W): 10.7" x 10.7" (27.2 x 27.2 cm) | C383 | DK 2.799,00 |
| C583  | 8" Micro-Ceramic Composite (MCC) cone, cast-Aluminum frame woofer <ul style="list-style-type: none"> • 1" Aluminum dome swiveling tweeter with waveguide • 3-position HF level control • Mounting depth: 5.2" (13.2 cm) • Weight: 2.8 lb (1.3 kg) / Shipping weight: 3.8 lb (1.7 kg) • Cutout dimensions (dia.): 9.6" (24.4 cm) • Nominal impedance: 8 Ohms • Recommended amplifier power range: 10 - 135 watts • Sensitivity: 88 dB (2.83V/1m) • Frequency range: 45Hz - 25kHz (-3 dB); 30Hz - 30kHz (-10dB) • Includes both round and square zero-bezel magnetic grilles • Round grille finished dimension (dia.): 10.7" (27.2 cm) • Square grille finished dimensions (H x W): 10.7" x 10.7" (27.2 x 27.2 cm) | C583 | DK 3.699,00 |
| C783  | 8" Micro-Ceramic Composite (MCC) cone, cast-Aluminum frame high-output woofer <ul style="list-style-type: none"> • 1" Aluminum dome swiveling high-output tweeter with waveguide • 3-position HF level control • LF boundary compensation • Mounting depth: 5.2" (13.2 cm) • Weight: 3.1 lb (1.4 kg) / Shipping weight: 4.1 lb (1.9 kg) • Cutout dimensions (dia.): 9.6" (24.4 cm) • Nominal impedance: 8 Ohms • Recommended amplifier power range: 10 - 150 watts • Sensitivity: 88 dB (2.83V/1m) • Frequency range: 36Hz - 28kHz (-3 dB); 25Hz- 35kHz (-10dB) • Includes both round and square zero-bezel magnetic grilles • Round grille finished dimension (dia.): 10.7" (27.2 cm) • Square grille finished dimensions (h x w): 10.7" x 10.7" (27.2 x 27.2 cm) | C783 | DK 4.899,00 |
| Rough-in Bracket | RIB for all Cx83 8 ½" In-Ceiling Loudspeakers | PCK8C | DK 256,00 |
| Fire-Rated Back-box | Fire (1 hour) and Plenum Rated Steel Backbox for all Cx83 8 ½" In-Ceiling Loudspeakers | FBB8C | DK 1.499,00 |

| Model | Product Description | Part # | SALGSPRIS |
|---|--|--------|-------------|
| <p>W253L</p>  | <p>Two 5" Aluminum cone, cast-Aluminum frame woofers</p> <ul style="list-style-type: none"> • Can be mounted vertical or horizontal for L-C-R applications • 1" Aluminum dome swiveling tweeter with waveguide • Nominal impedance: 8 Ohms • Recommended amplifier power range: 10 - 130 watts • Sensitivity: 91 dB (2.83V/1m) • Frequency range: 55Hz -18kHz (-3 dB); 40Hz - 20kHz (-10dB) • Mounting depth: 3.5" (8.8 cm) • Weight: 5.6 lb (2.5 kg) / shipping weight: 7.3 lb (3.3 kg) • Cutout dimensions (H x W): 14.1" x 6.4" (35.9 cm x 16.3 cm) • Includes zero-bezel magnetic grille • Grille finished dimensions (H x W): 15.1" x 7.4" (38.4 cm x 18.8 cm) • C-2 fastening mechanism • Compatible with wall material thickness range: 0.5" – 2.0" (1.3 – 5.0 cm) | W253L | DK 2.399,00 |
| | | | |
| | | | |
| | | | |



In-Ceiling and In-Wall Architectural Loudspeakers



| Model | Product Description | Part # | SALGSPRIS/stk |
|--|---|--------|---------------|
| W263  | 6 ½" Aluminum cone, cast-polymer frame woofer <ul style="list-style-type: none"> • 1" Aluminum dome swiveling tweeter with waveguide • Mounting depth: 3.5" (8.8 cm) • Weight: 3.4 lb (1.5 kg) / shipping weight: 4.9 lb (2.2 kg) • Includes zero-bezel magnetic grille • Grille finished dimension (H x W): 10.8" x 8.3" (27.3 cm x 21.1 cm) • Cutout dimensions (H x W): 9.8" x 7.3" (24.9 cm x 18.5 cm) • Nominal impedance: 8 Ohms • Recommended amplifier power range: 10 - 100 watts • Sensitivity: 88 dB (2.83V/1m) • Frequency range: 50Hz - 18kHz (-3 dB); 35Hz - 20kHz (-10dB) | W263 | DK 1.199,00 |
| W363  | 6 ½" Micro-Ceramic Composite (MCC) cone, cast-polymer frame woofer <ul style="list-style-type: none"> • 1" Aluminum dome swiveling tweeter with waveguide • Mounting depth: 3.6" (9.1 cm) • Weight: 3.8 lb (1.7 kg) / Shipping weight: 4.9 lb (2.2 kg) • Cutout dimensions (H x W): 9.8" x 7.3" (24.9 cm x 18.5 cm) • Includes zero-bezel magnetic grille • Grille finished dimension (H x W): 10.8" x 8.3" (27.3 cm x 21.1 cm) • Nominal impedance: 8 Ohms • Recommended amplifier power range: 10 - 120 watts • Sensitivity: 88 dB (2.83V/1m) • Frequency range: 55Hz - 22kHz (-3 dB); 40Hz - 30kHz (-10dB) | W363 | DK 1.999,00 |
| W563  | 6 ½" Micro-Ceramic Composite (MCC) cone, cast-Aluminum frame woofer <ul style="list-style-type: none"> • 1" Aluminum dome swiveling tweeter with waveguide • 3-position HF level control • Mounting depth: 3.7" (9.4 cm) • Weight: 4.4 lb (2 kg) / shipping weight: 5.5 lb (2.5 kg) • Cutout dimensions (H x W): 9.8" x 7.3" (24.9 cm x 18.5 cm) • Includes zero-bezel magnetic grille • Grille finished dimension (H x W): 10.8" x 8.3" (27.3 cm x 21.1 cm) • Nominal impedance: 8 Ohms • Recommended amplifier power range: 10 - 130 watts • Sensitivity: 88 dB (2.83V/1m) • Frequency range: 50Hz - 25kHz (-3 dB); 35Hz - 30kHz (-10dB) | W563 | DK 2.877,00 |
| W763  | 6 ½" Micro-Ceramic Composite (MCC) cone, cast-Aluminum frame high-output woofer <ul style="list-style-type: none"> • 1" Aluminum dome swiveling high-output tweeter with waveguide • 3-position HF level control • LF boundary compensation • Mounting depth: 3.6" (9.1 cm) • Weight: 5.4 lb (2.5 kg) / shipping weight: 6.5 lb (3.0 kg) • Cutout dimensions (H x W): 9.8" x 7.3" (24.9 cm x 18.5 cm) • Includes zero-bezel magnetic grille • Grille finished dimension (H x W): 10.8" x 8.3" (27.3 cm x 21.1 cm) • Nominal impedance: 8 Ohms • Recommended amplifier power range: 10 - 140 watts • Sensitivity: 89 dB (2.83V/1m) • Frequency range: 45Hz - 28kHz (-3 dB); 30Hz - 35kHz (-10dB) | W763 | DK 4.099,00 |
| Rough-In Brackets | RIB for all Wx63 6 ½" In-Wall Loudspeakers | PCK6 | DK 179,00 |
| Fire-Rated Back-box | Fire (1 hour) and Plenum Rated Steel Back-box for Wx63 In-Wall Loudspeaker | FBB6 | DK 899,00 |





In-Ceiling and In-Wall Architectural Loudspeakers



| Model | Product Description | Part # | SALGSPRIS/stk | |
|---|---|---|---------------|-------------|
| W873  | 7" Micro-Ceramic Composite (MCC) cone, cast-Aluminum frame high-output woofer <ul style="list-style-type: none"> • 1" Aluminum dome swiveling high-output tweeter with waveguide • 3-position HF level control • LF boundary compensation • Advanced high-order crossover network • Mounting depth: 3.7" (9.4 cm) • Weight: 7.5 lb (3.4 kg) / shipping weight: 9.0 lb (4.1 kg) • Cutout dimensions (H x W): 12.1" x 10.2" (30.6 cm x 25.9 cm) • Includes zero-bezel magnetic grille • Grille finished dimension (H x W): 13.0" x 11.1" (33.0 cm x 28.2 cm) • C-2 fastening mechanism • Compatible with wall material thickness range: 0.5" – 2.0" (1.3 – 5.0 cm) • Nominal impedance: 8 Ohms • Recommended amplifier power range: 10 - 150 watts • Sensitivity: 86 dB (2.83V/1m) • Frequency range: 40Hz - 28kHz (-3 dB); 30Hz - 35kHz (-10dB) | W873 | DK 7.348,00 | |
| | Rough-In Brackets | RIB for W873 In-Wall Loudspeaker | PCK7 | DK 179,00 |
| | Fire-Rated Back-box | Fire (1 hour) and Plenum Rated Steel Back-box for W873 In-Wall Loudspeaker | FBB7 | DK 1.156,00 |
| W970  | 7" Micro-Ceramic Composite (MCC) cone, cast-Aluminum frame high-output woofer <ul style="list-style-type: none"> • 1" Aluminum dome high-output tweeter with waveguide • HF level & tilt controls • LF boundary compensation, & listener axis controls • Advanced high-order crossover network • Cast aluminum baffle with multi-point spring loaded clamping mechanism • Mounting depth: 3.7" (9.4 cm) • Weight: 12.6 lb (5.7 kg) / shipping weight: 14.6 lb (6.6 kg) • Cutout dimensions (H x W): 14.9" x 10.5" (37.8 cm x 26.7 cm) • Includes zero-bezel magnetic grille • Grille finished dimension (H x W): 16.3" x 12.1" (41.4 cm x 30.7 cm) • Nominal impedance: 8 Ohms • Recommended amplifier power range: 10 - 150 watts • Sensitivity: 88 dB (2.83V/1m) • Frequency range: 40Hz - 28kHz (-3 dB); 30Hz - 35kHz (-10dB) | REVEL W970 | DK 10.099,00 | |
| | Rough-In Brackets | RIB for W970 In-Wall Loudspeaker | PCK81 | DK 513,00 |
| | Fire-Rated Back-box | Fire (1 hour) and Plenum Rated Steel Back-box for W970 In-Wall Loudspeaker | FBB81 | DK 1.799,00 |



In-Ceiling and In-Wall Architectural Loudspeakers



| Model | Product Description | Part # | SALGSPRIS/stk |
|--|--|---|---------------|
| W283  | 8" Aluminum cone, cast-polymer frame woofer <ul style="list-style-type: none"> • 1" Aluminum dome swiveling tweeter with waveguide • Mounting depth: 3.7" (9.4 cm) • Weight: 4.4 lb (2 kg) / shipping weight: 6.3 lb (3 kg) • Cutout dimensions (H x W): 11.9" x 8.9" (30.3 cm x 22.7 cm) • Includes zero-bezel magnetic grille • Grille finished dimension (H x W): 12.9" x 9.9" (32.8 cm x 25.2 cm) • Nominal impedance: 8 Ohms • Recommended amplifier power range: 10 - 100 watts • Sensitivity: 88 dB (2.83V/1m) • Frequency range: 37Hz - 18kHz (-3 dB); 29Hz - 20kHz (-10dB) | W283 | DK 1.644,00 |
| W383  | 8" Micro-Ceramic Composite (MCC) cone, cast-polymer frame woofer <ul style="list-style-type: none"> • 1" Aluminum dome swiveling tweeter with waveguide • Mounting depth: 3.7" (9.4 cm) • Weight: 4.9 lb (2.2 kg) / shipping weight: 6.3 lb (2.9 kg) • Cutout dimensions (H x W): 11.9" x 8.9" (30.3 cm x 22.7 cm) • Includes zero-bezel magnetic grille • Grille finished dimension (H x W): 12.9" x 9.9" (32.8 cm x 25.2 cm) • Nominal impedance: 8 Ohms • Recommended amplifier power range: 10 - 125 watts • Sensitivity: 89 dB (2.83V/1m) • Frequency range: 45Hz - 22kHz (-3 dB); 35Hz - 30kHz (-10dB) | W383 Note: Ask sales rep for available discount on RollerLock model W380 | DK 2.877,00 |
| W583  | 8" Micro-Ceramic Composite (MCC) cone, cast-Aluminum frame woofer <ul style="list-style-type: none"> • 1" Aluminum dome swiveling tweeter with waveguide • 3-position HF level control • Mounting depth: 3.8" (9.6 cm) • Weight: 6.4 lb (2.9 kg) / shipping weight: 7.7 lb (3.5 kg) • Cutout dimensions (H x W): 11.9" x 8.9" (30.3 cm x 22.7 cm) • Includes zero-bezel magnetic grille • Grille finished dimension (H x W): 12.9" x 9.9" (32.8 cm x 25.2 cm) • Nominal impedance: 8 Ohms • Recommended amplifier power range: 10 - 135 watts • Sensitivity: 89 dB (2.83V/1m) • Frequency range: 40Hz - 25kHz (-3 dB); 30Hz - 30kHz (-10dB) | W583 Note: Ask sales rep for available discount on RollerLock model W580 | DK 3.699,00 |
| W783  | 8" Micro-Ceramic Composite (MCC) cone, cast-Aluminum frame high-output woofer <ul style="list-style-type: none"> • 1" Aluminum dome swiveling high-output tweeter with waveguide • 3-position HF level control • LF boundary compensation • Mounting depth: 3.7" (9.4 cm) • Weight: 7.1 lb (3.2 kg) / Shipping weight: 8.6 lb (3.9 kg) • Cutout dimensions (H x W): 11.9" x 8.9" (30.3 cm x 22.7 cm) • Includes zero-bezel magnetic grille • Grille finished dimension (H x W): 12.9" x 9.9" (32.8 cm x 25.2 cm) • Nominal impedance: 8 Ohms • Recommended amplifier power range: 10 - 150 watts • Sensitivity: 89 dB (2.83V/1m) • Frequency range: 36Hz - 28kHz (-3 dB); 25Hz - 35kHz (-10dB) | W783 Note: Ask sales rep for available discount on RollerLock model W780 | DK 4.899,00 |
| Rough-In Brackets | RIB for all 8" In-Wall Loudspeakers | PCK8 | DK 215,00 |
| Fire-Rated Back-box | Fire (1 hour) and Plenum Rated Steel Back-box for Wx83 In-Wall Loudspeaker | FBB8 | DK 880,00 |

In-Ceiling and In-Wall Architectural Loudspeakers



| Model | Product Description | Part # | SALGSPRIS/stk |
|---|---|------------|---------------|
| W893  | 9" Micro-Ceramic Composite (MCC) cone, cast-Aluminum frame high-output woofer <ul style="list-style-type: none"> • 3.5" micro-ceramic composite (MCC) cone, cast-aluminum frame high-output midrange • 1" Aluminum dome swiveling high-output tweeter with waveguide • 3-position HF level control • LF boundary compensation • Advanced high-order crossover network • Mounting depth: 3.7" (9.4 cm) • Weight: 10.8 lb (4.9 kg) / shipping weight: 12.8 lb (5.8 kg) • Cutout dimensions (H x W): 17.4" x 11.6" (44.3 cm x 29.5 cm) • Includes zero-bezel magnetic grille • Grille finished dimension (H x W): 18.5" x 12.7" (47.0 cm x 32.3 cm) • C-2 fastening mechanism • Compatible with wall material thickness range: 0.5" – 2.0" (1.3 cm – 5.0 cm) • Nominal impedance: 8 Ohms • Recommended amplifier power range: 10 - 200 watts • Sensitivity: 89 dB (2.83V/1m) • Frequency range: 32Hz - 28kHz (-3 dB); 23Hz - 35kHz (-10dB) | W893 | DK 8.199,00 |
| | RIB for W893 In-Wall Loudspeaker | PCK9 | DK 256,00 |
| | Fire (1 hour) and Plenum Rated Steel Back-box for W873 In-Wall Loudspeaker | FBB9 | DK 1.156,00 |
| W990  | 9" Micro-Ceramic Composite (MCC) cone, cast-Aluminum frame high-output woofer <ul style="list-style-type: none"> • 1" Aluminum dome high-output tweeter with waveguide • HF level & tilt controls • LF boundary compensation, & listener axis controls • Advanced high-order crossover network • Cast aluminum baffle with multi-point spring loaded clamping mechanism • Mounting depth: 3.7" (9.4 cm) • Weight: 17.0 lb (7.7 kg) / shipping weight: 19.4 lb (8.8 kg) • Cutout dimensions (H x W): 19.1" x 12.5" (48.6 cm x 31.8 cm) • Includes zero-bezel magnetic grille • Grille finished dimension (H x W): 20.6" x 13.9" (52.3 cm x 35.3 cm) • Nominal impedance: 8 Ohms • Recommended amplifier power range: 10 - 200 watts • Sensitivity: 89 dB (2.83V/1m) • Frequency range: 32Hz - 28kHz (-3 dB); 23Hz - 35kHz (-10dB) | REVEL W990 | DK 14.299,00 |
| | RIB for W990 In-Wall Loudspeaker | PCK941 | DK 513,00 |
| | Fire (1 hour) and Plenum Rated Steel Backbox for W990 In-Wall Loudspeaker | FBB941 | DK 1.670,00 |

| | |
|--------------------------------------|---|
| Note on Fire Rated Back Boxes | <p>Check local fire and building codes for the type of wall construction and thickness required to meet appropriate fire ratings.</p> <p>Standards and Ratings Tested (Subject to Change)</p> <p>a) ASTM E 119-00 REV A 2000-07-10 and E119-05 Standard Test Methods for Fire Tests of Building Construction and Materials</p> <p>b) NFPA 251 1999-00-00 Standard Methods of Tests of Fire Endurance of Building Construction and Materials(National Fire Codes, vol. 6)</p> <p>c) UL 263 1997-02-27 UL Standard for Safety Fire Tests of Building Construction and Materials Twelfth Edition; Reprint with Revisions Through and including 06/02/1998</p> <p>d) ULC CAN/ULC-S101 -M89 1989-00-00 and UBC 7-1 Standard Methods of Fire Endurance Tests of Building Construction and Materials</p> <p>e) UL 2043 1996-12-02 UL Standard for Safety Fire Test for Heat and Visible Smoke Release for Discrete Products and Their Accessories Installed in Air-Handling Spaces Second Edition; Reprint with Revisions Through and Including June 27, 2001</p> |
|--------------------------------------|---|



Bülow:Steensen A/S – Øster Kringelvej 32 - 8250 Egå
Tlf.: +45 86216618 - +45 86136618 Mobil: +45 40278818 – Mail cb@bulowsteensen.dk
Bank: Middelfart Sparekasse - Kontonr.: 1687/3222246333 IBAN-nr.: DK1516873222246333 - SWIFT-kode: MISPDK21